

FILETTATURA GAS CILINDRICA

(conforme a ISO 228)

Dimen.	Passo F x 1"	Filettatura interna		Filettatura esterna	
		∅ Foratura		∅ Tornitura	
		min.	max.	max	min.
G 1/8'	28	8,566	8,848	9,728	9,514
G 1/4'	19	11,445	11,890	13,157	12,907
G 3/8'	19	14,950	15,395	16,662	16,412
G 1/2'	14	18,631	19,172	20,955	20,671
G 5/8'	14	20,587	21,128	22,911	22,627
G 3/4'	14	24,117	24,658	26,441	26,157
G 7/8'	14	27,877	28,418	30,201	29,917
G 1"	11	30,291	30,931	33,249	32,889
G 1 1/8	11	34,939	35,579	37,897	37,357
G 1 1/4	11	38,952	39,592	41,910	41,550
G 1 3/8	11	41,365	42,005	44,343	43,963
G 1 1/2	11	44,845	45,485	47,803	47,443
G 1 3/4	11	50,788	51,428	53,746	53,386
G 2"	11	56,656	57,296	59,614	59,254
G 2 1/4	11	62,752	63,392	65,710	65,276
G 2 1/2	11	72,226	72,866	75,184	74,750
G 2 3/4	11	78,576	79,216	81,534	81,100
G 3"	11	84,926	85,566	87,884	87,450